



1-800-238-0333

WIRE ROPE

19 X 7

[Click here for
Warnings & Specifications](#)

| Item No. | Diameter | Grade | Breaking Strength | Weight | Bulk Quantity |
|--------------|----------|-------|-------------------|-----------|---------------|
| 002300-00010 | 1/4 | EIPS | 2.77 tons | .113 / ft | 5000' |
| 002300-00020 | 5/16 | EIPS | 4.30 tons | .177 / ft | 5000' |
| 002300-00030 | 3/8 | EIPS | 6.15 tons | .25 / ft | 5000' |
| 002300-00040 | 7/16 | EIPS | 8.33 tons | .35 / ft | 5000' |
| 002300-00050 | 1/2 | EIPS | 10.8 tons | .45 / ft | 5000' |
| 002300-00060 | 9/16 | EIPS | 13.6 tons | .58 / ft | 5000' |
| 002300-00070 | 5/8 | EIPS | 16.8 tons | .71 / ft | 5000' |
| 002300-00080 | 3/4 | EIPS | 24.0 tons | 1.02 / ft | 5000' |
| 002300-00090 | 7/8 | EIPS | 32.5 tons | 1.39 / ft | 5000' |
| 002300-00095 | 1 | EIPS | 42.2 tons | 1.82 / ft | 5000' |

LOCATIONS

Chicago · Houston · Kansas City
Los Angeles · Olive Branch
Philadelphia · Seattle · Tampa

A DIVISION OF
HWC
HOUSTON WIRE & CABLE COMPANY

Reels under 500' please add 10% to the cut length price.

Actual operating loads may vary – NEVER exceed the recommended design factor or 20% of catalog strength.

Made in accordance with federal specification RR-W-410D.

19 x 7 is recommended for hoists using a single-part line.

The rotation resistant properties of 19 x 7 are greater than 8 x 25.

For more information, please click on the warnings & specifications link above.

RIGHT PRODUCT · RIGHT PLACE · RIGHT TIME®