



1-800-238-0333

WIRE ROPE

8 X 25

[Click here for
Warnings & Specifications](#)

Item No.	Diameter	Grade	Breaking Strength	Weight	Bulk Quantity
002300-00100	3/8	EIPS	6.6 tons	.26 / ft	5000'
002300-00110	1/2	EIPS	11.6 tons	.47 / ft	5000'
002300-00120	9/16	EIPS	14.7 tons	.60 / ft	5000'
002300-00130	5/8	EIPS	18.1 tons	.73 / ft	5000'
002300-00140	3/4	EIPS	25.9 tons	1.06 / ft	5000'
002300-00150	7/8	EIPS	35.0 tons	1.44 / ft	5000'

LOCATIONS

Chicago · Houston · Kansas City
Los Angeles · Olive Branch
Philadelphia · Seattle · Tampa

A DIVISION OF
HWC
HOUSTON WIRE & CABLE COMPANY

Reels under 500' please add 10% to the cut length price.

Actual operating loads may vary – NEVER exceed the recommended design factor or 20% of catalog strength.

Made in accordance with federal specification RR-W-410D.

19 x 7 is recommended for hoists using a single-part line.

The rotation resistant properties of 19 x 7 are greater than 8 x 25.

For more information, please click on the warnings & specifications link above.

RIGHT PRODUCT • RIGHT PLACE • RIGHT TIME®