

SYNTHETIC SLINGS
Multi-Leg Bridle

TYPE 10

MULTI-LEG BRIDLE								
Web Width (in.)	Number of Legs	Rec. Oblong Size (in.)	Rec. Alloy Eye Hook	Rated Capacities in Pounds				
				Vertical	@ 60°	@ 45°	@ 30°	
1	1	1/2	1 ton	1,600				1 PLY
1	2	1/2	1 ton		2,700	2,200	1,600	
1	3	3/4	1 ton		4,100	3,300	2,400	
1	4	1	1 ton		5,500	4,500	3,200	
2	1	1/2	1 1/2 ton	3,000				
2	2	3/4	1 1/2 ton		5,100	4,200	3,000	
2	3	1	1 1/2 ton		7,700	6,300	4,500	
2	4	1	1 1/2 ton		10,300	8,400	6,000	
1	1	1/2	1 1/2 ton	3,000				2 PLY
1	2	3/4	1 1/2 ton		5,100	4,200	3,000	
1	3	3/4	1 1/2 ton		7,700	6,300	4,500	
1	4	1	1 1/2 ton		10,300	8,400	6,000	
2	1	3/4	3 ton	6,000				
2	2	1	3 ton		10,300	8,400	6,000	
2	3	1	3 ton		15,500	12,700	9,000	
2	4	1 1/4	3 ton		20,700	16,900	12,000	



- Other sizes and configurations available upon request
- Capacities listed above correspond with the recommended hardware above. If oblong or hook sizes are changed capacities may change.
- Do not use slings at angles less than 30 degrees
- Do not exceed rated capacities

WARNING
 Do not exceed rated capacities. Sling capacity decreases as the angle decreases. Do not use at an angle less than 30° from horizontal.