

Wide Body and Load Balancer Web Slings

TYPE 8



WIDE BODY BASKET

	Type 8 (WB)	Body Width (in.)	Rated Capacity Vertical Basket (lbs.)	Eye Length (in.)	Eye Width (in.)	Min. Sling Length (in.)
1 PLY	WB1-906	6	15,400	9	1 1/2	40
	WB1-908	8	20,400	12	2	46
	WB1-912	12	30,800	18	3	60
	WB1-916	16	38,000	24	3	72
	WB1-920	20	45,000	30	3 1/2	90
	WB1-924	24	52,000	36	4	100
	WB1-930	30	45,000	48	4	120
2 PLY	WB2-906	6	28,600	9	1 1/2	40
	WB2-908	8	38,000	12	2	46
	WB2-912	12	57,200	18	3	60
	WB2-916	16	75,000	24	3 1/2	72
	WB2-920	20	90,000	30	5	90
	WB2-924	24	110,000	36	6	100
	WB2-930	30	90,000	48	6	120
	WB2-936	36	90,000	54	6	144

TYPE 9



LOAD BALANCER BASKET

	Type 9 (LBA)	Body Width (in.)	Rated Capacity Vertical Basket (lbs.)	Eye Length (in.)	Eye Width (in.)	Min. Sling Length (in.)
1 PLY	LBA1-906	6	5,000	9	1	44
	LBA1-908	8	5,000	9	1	44
	LBA1-910	10	5,000	12	1	54
	LBA1-912	12	5,000	12	1	54
	LBA1-916	16	10,000	12	2	54
	LBA1-920	20	10,000	18	2	66
	LBA1-924	24	10,000	18	2	66
2 PLY	LBA2-906	6	10,000	10	1	44
	LBA2-908	8	10,000	10	1	44
	LBA2-910	10	10,000	12	1	54
	LBA2-912	12	10,000	12	1	54
	LBA2-916	16	18,000	12	2	54
	LBA2-920	20	18,000	18	2	66
	LBA2-924	24	18,000	18	2	66

- Not recommended to be used in choker configuration.
- Rated capacities are vertical (90°) basket. Capacity decreases as angle decreases as angle decreases. Do not use at angle less than 30° from horizontal.

- Not recommended to be used in choker configuration.
- Rated capacities are vertical (90°) basket. Capacity decreases as angle decreases as angle decreases. Do not use at angle less than 30° from horizontal.



WARNING
Do not exceed rated capacities. Sling capacity decreases as the angle decreases. Do not use at an angle less than 30° from horizontal.